Filed: September 10, 2004

IN THE CLAIMS:

Please amend claims 1, 2, 4, 11, 20 and 22 of the above-identified application as follows.

1. (Currently Amended) A device for the supply of a gas to an area, comprising: a supply conduit, which is connectable to a gas source and which includes an outlet end, and a porous body, which is manufactured of a foam rubber-like material and is provided at said outlet end, wherein the device is arranged to permittransmit said supply of gas through the porous body to create a protective gas atmosphere in the area, the device includes an attachment member, which includes a first surface and a second surface and a continuous channel extending through the surfaces econd and first surfaces, respectively, wherein the porous body is attached to said first surface and wherein the outlet end is connected to the attachment member for permitting transmitting said supply viain a direction through said outlet end, said channel and said porous body, respectively, for creating said protective gas atmosphere.

- 2. (Currently Amended) A device according to claim 1, wherein said first surface of the attachment member covers substantially the whole porous body seen in a first direction extending from the attachment member through the body.
 - 3. (Previously Presented) A device according to claim 1, wherein

Filed: September 10, 2004

the attachment member includes a sleeve, which extends outwardly away from the

porous body and which is connected to the outlet end, wherein the channel extends

through the sleeve.

4. (Currently Amended) A device according to claim 23, wherein

the sleeve extends in a direction forming an angle to the first direction x, wherein

said angle is 0 to 90°.

5. (Previously Presented) A device according to claim 3, wherein

the supply conduit projects into the sleeve, or that the sleeve projects into the

supply conduit.

6. (Previously Presented) A device according to claim 2, wherein

the attachment member and the porous body are substantially circular seen in the

first direction x.

7. (Previously Presented) A device according to claim 6, wherein

the porous body has a substantially semispherical surface which faces away from

the attachment member.

8. (Previously Presented) A device according to claim 1, wherein

the supply conduit includes at least a first conduit portion with a casing of a

3

Filed: September 10, 2004

material, which has a large flexibility, and with a means for stiffening, which extends along the casing and has a lower flexibility than the casing.

9. (Previously Presented) A device according to claim 8, wherein the stiffening means is plastically deformable.

10. (Previously Presented) A device according to claim 8, wherein the stiffening means includes a metal wire.

11. (Currently Amended) A device according to claim 8, wherein the stiffening means extend extends substantially freely within the first conduit portion of the supply conduit.

12. (Cancelled)

13. (Previously Presented) A device according to claim 1, wherein the foam rubber-like material includes polyurethane foam with open cells.

14. (Cancelled)

15. (Previously Presented) A device according to claim 1, wherein the porous body includes a homogenous body.

Filed: September 10, 2004

16. (Previously Presented) A device according to claim 1, wherein

the device includes a filter, which is arranged on the supply conduit for filtering

said gas flowing through the supply conduit.

17. (Previously Presented) A device according to claim 1, wherein

said gas includes a main component which is carbon dioxide.

18. (Previously Presented) A device according to claim 1, wherein

the porous body is arranged to supply said gas in a control flow in order to enable

deformation of a gas cushion, which is intended to substantially fill a volume at

said area and thus prevents air from the surroundings to reach said area.

19. (Previously Presented) A device according to claim 1, wherein

said area adjoins an inner portion of the body of a human being or an animal,

which portion is open outwardly towards the surroundings, wherein the porous

body is arranged to be located at said outwardly open inner portion.

20. (Currently Amended) A device for the supply of a gas to an

area, comprising:

a supply conduit connectable to a gas source, including an outlet

end;

5

Serial No.: 10/507,467 Filed: September 10, 2004

an attachment member <u>connected to said outlet end and</u> including a first surface, a second surface located opposite said first surface, and a <u>centrally</u> <u>located continuous</u> channel configured for receiving said supply conduit and extending through both said second and first surfaces, respectively; and

a porous body provided at said outlet end and having a proximal end attached to said first surface and a distal end free of attachment, the deviceporous body being in direct fluid communication with said supply conduit and arranged to permittransmit the supply of gas in a direction through the outlet end, the channel and the porous body, respectively, for creating a protective gas atmosphere in the area.

- 21. (Previously Presented) A device according to claim 20, wherein said porous body is manufactured of a permeable material including at least one of paper, felt, sinter metal and filter material.
- 22. (Currently Amended) A device for the supply of a gas to an area, comprising:

a supply conduit connectable to a gas source and including an outlet end;

an attachment member including a first surface, a second surface located opposite said first surface, a sleeve surrounding said conduit and directly projecting from said second surface; and a continuous channel extending through

Serial No.: 10/507,467 Filed: September 10, 2004

both-said sleeve and said second and first surfaces, respectively, and a sleeve surrounding said conduit and projecting from said second surface; and

a porous body projecting from said first surface in a direction opposite from said sleeve, said porous body having at least twice the thickness of said attachment member;

wherein said porous body is in <u>direct fluid</u> communication with said outlet end to <u>permittransmit</u> the supply of gas <u>in a direction</u> through said <u>outlet</u> end, said channel and said porous body, respectively, for creating a protective gas <u>atmosphere in the area</u>.